

32kg Stainless Steel Commercial Spreader

Unique Features

- **Heavy-Duty Construction:** The robust frame and axle are designed for commercial use, ensuring long-lasting durability even in demanding environments, with stainless steel providing enhanced corrosion resistance for extended product life.
- **Precision Rate Control:** The adjustable rate control plate with easy-to-read A-Z settings allows for accurate material application, reducing waste and improving results.
- **Pattern Adjustment System:** The discharge chute can be fine-tuned (settings A, B, C) for left/right pattern control, enabling precise coverage and minimising overlap.
- **Large Hopper Capacity:** The high-volume hopper holds up to 32kg, allowing for fewer refills during large jobs and increasing operational efficiency.
- **Dual Wheel Drive:** Identical drive and free wheels make assembly simple and ensure smooth, reliable operation across various terrains.
- **Deflector Plate:** The deflector accessory enables precise edge spreading, minimising waste on sidewalks, fence lines and roughs for cleaner application.



PRODUCT NAME	SUGGESTED RATES KG/HA		NITROGEN APPLIED KG/HA		LIVING TURF CBRIVSS		ACCUPRO		LESCO NUMBERS		LESCO LETTERS		EARTHWAY	
	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate
MP CARBON CAL	250	500	5	10	M	Q	O	S	14	18	F	H	17	22
MP CARBON GREEN	250	500	22.5	45	K	N	M	P	21	26	J	M	13	15
MP GREENS 24	200	300	48	72	H	J	H	I	10	12	C 1/2	D 1/2	9	11
MP GREEN STARTER	150	240	24	38.4	F	G	G 1/2	I	8	9	C	C 1/2	9 1/2	11
MP GREENS 10	220	300	22	30	G	I	H	H 1/2	9	11	C 1/2	D	9	10
MP HUMOXY EC+	250	500	0	0	F	J	H	L	15	19	E	I	10	14
MP SPECTRUM MINI	150	300	30	60	I	N	K 1/2	P	11	15	D 1/2	H	13	18
MP SUPER CARBON MINI	250	500	0.25	0.5	L	O	M 1/2	P 1/2	13	16	E 1/2	G	15 1/2	18 1/2
GYPSUM	180	350	0	0	M	O	N 1/2	P 1/2	14	16	I	L	16	18

PRODUCT NAME	SUGGESTED RATES KG/HA		NITROGEN APPLIED KG/HA		LIVING TURF CBRIVSS		ACCUPRO		LESCO NUMBERS		LESCO LETTERS		EARTHWAY	
	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate	Low rate	High rate
MP N-DURE	100	150	46	69	G	H	H 1/2	I 1/2	9	10	C 1/2	D	10 1/2	11 1/2
MP ORIGIN	180	270	50.4	75.6	N	Q	P	S	16	21	H	K	18	22
MP PREPLANT	200	250	40	50	K	N	M	P	15	17	G	K	15	18
MP PRO 22	180	300	39.6	66	H	I	I ½	K	10	11	D	D ½	11 ½	13
MP PRO 31	180	250	55.8	77.5	N	Q	P	S	16	21	H	K	18	22
MP SPECTRUM	150	300	30	60	K	N	M	P	15	17	G	K	15	18
MP TURF STARTER	180	300	32.4	54	K	N	M	P	15	17	G	K	15	18
MP TURFSTARTER	125	250	16.25	32.5	H	J	J	K 1/2	10	11	D	D 1/2	12	13 1/2
MESA 30	80	140	24	42	I	F	K	H	17	15	I	G	15	14
MESA XP	125	225	25	45	F	N	H	N	16	14	H	F	10	16
UMAXX	110	150	50.6	69	G	H	H 1/2	I 1/2	9	10	C 1/2	D	10 1/2	11 1/2